

LTE Fleet Solutions® Standard Features		LTE Fleet Solutions® Additional Available Options
Length	45' or 48'	
Side & Overall Height	12'6"/13'	
Open-Top	Yes	
Width	102"	
Box	Std. Build	
Wheel Wells	No	
5th Wheel Height	48"	
Kingpin Setting	36"	
Upper Coupler	Domex With Grease Saver Rods	
Panels	.063" - White	Black With Matching Door
Post Centers	14.75"	
Crossmembers	Steel	
Crossmember Centers	14.5"	
Landing Gear	Jost 2-Speed	
Subframe	Slider Rail	
Undercarriage Finish	Black Undercoat	
Suspension	AR Slider	
Axles	TP	
Axle Centers	49"	
Manual Air Dump	Mounted at Slide Box	
Hub & Drum	Steel Hub - Cast Drum	
Brakes	16.5" X 7" Q-Series	
Rim	Hub-Pilot - Unimount	
Wheels	Steel - White Finish	(8) Alcoa Polished Aluminum
Tires	Kelly	Any Brand, Any Size
ABS Brakes	1S/2M (2) Wheels	
Mud-Flaps	Anti-Spray - Anti Sail	
Drive Unit	Keith 3" RFII DX Drive	
Flooring	Perfect Seal Overlap MD	UHMW
Subfloor	Aluminum	
T-Blocks	UHMW	
Hydraulic Hoses	(2) 3/4" X 10'	
Hydraulic Fittings	Choice	
Slope Board	Removable	
Side Seal	Flat Aluminum	
Nose	Inverted 4 1/4"	
Nose Finish	Smooth	
Catwalk	No	
Ladders	Std. Ladder	
Rear Unit	Aluminum	
Bumper	Std. DOT Aluminum	
Doors	Double Composite	
Door Latch	(2) Steel Rods (Each Door)	
Tarps	18 oz., Choice of Color	
Tarp System	Shur-Lok	
Tarp Crank	Rear Slip With Flex	
Tarp Bows	(4) 1"X2" - 6" Arch	
Air Scale	Main	
Electrical	(1) Grote Main 7-Way	
Lighting	Grote High Count LED	

Other Popular Options Not Listed, But Not Limited To: Added Safety Features, Rear Header Turn Signal (1) on Each Side

WS = Weight Saver